



301 Ellicott Street
Buffalo, NY 14203-1680
800.724.7667
716.854.2889
www.emulso.com

SOLVALL

PRODUCT DESCRIPTION

This sealant & asphalt remover is a ready-to-use, water rinsable liquid, which easily removes coal tar sealer, asphalt sealer, crack sealer, roofing tar, mastic, tack coat, or oil and grease from most washable surfaces. It can be safely used on tools, equipment, vehicles, sidewalks, flooring, siding, clothing and carpeting. Solvall will clean up fresh spills, splatters and oversprays, as well as caked-on messes.

USES

- Tools & Equipment
- Vehicles
- Carpeting & Clothing
- Flooring & Siding
- Sidewalks



SPECIFICATIONS

Solvall is a clear liquid industrial solvent blend with a combination fragrance/solvent odor. It contains 100% active ingredients with no water and is non-flammable. When applied on the surface of unwanted soils, Solvall will breakdown the composition of the stain and emulsify it so that it may be rinsed away with clear water. It is non-foaming and evaporates slowly.

APPLICATION

Rate of application and coverage will vary depending on conditions. Successful application can be achieved by a number of methods. Solvall should be used full strength. For hard surfaces such as concrete, metal, wood, glass, masonry, ceramic, stone, etc., the object may be sprayed, poured, brushed, blotted, or soaked with Solvall. Allow time for Solvall to work, agitate with a rag or stiff bristle brush and rinse away stain and residue with water. Repeat as needed. For quicker results, thicker soils can be scraped to remove heavy deposits prior to application.

Tools and equipment must be solvent resistant. Note: Objects to be cleaned should first be tested for compatibility, especially on paints and plastics. Do not use on plastic unless they are solvent resistant. When cleaning tile floor surfaces, Solvall will also remove floor finishes. If left on for an extended period of time, it may damage the flooring material. After cleaning, all residue should be thoroughly rinsed from the surface using clean water. Solvall should not be used to clean asphalt surfaces.

Item No.	Description
G11-G	Solvall - 1 Gallon
G11-5G	Solvall - 5 Gallon Pail
G11-4CS	Solvall - 4 Gallon Case
G11-QCS	Solvall - 12 Quart Case
G11-55	Solvall - 55 Gallon Drum