

# GLAZE

## Floor Finish



**GLAZE** uses a high-performance acrylic-based formula to quickly seal floors with minimal finish maintenance required. **GLAZE** is formulated to be buffed once a week or less & contains high solids.

- Seals Floors with a High Shine Finish
- Easy Maintenance! Buff Once Weekly After Application
- Fast Dry Time
- High Solids



**LOW MAINTENANCE FORMULA! BUFF ONCE WEEKLY AFTER FIRST APPLICATION.**



## WHERE TO USE

- FLOORS

## DIRECTIONS

**READ ENTIRE PRODUCT LABEL PRIOR TO USE.**

**FLOOR PREPARATION:** If stripping is necessary, use a high-quality stripper & follow directions accordingly. If floor is in good condition & stripping is not necessary, sweep floor then wash with a neutral floor cleaner to remove dirt & soil. Follow with a thorough rinse & allow floor to dry completely.

**APPLICATION:** Apply 2-3 liberal coats of **GLAZE** using a clean mop. Allow dry time between coats. Apply additional coats to achieve desired gloss finish. If high shine is desired, 24-hours after application buff floor at 175 RPMs. **GLAZE** can be high-speed burnished at 1500-2000 RPMs.

**BURNISHING:** Dust mop & wash floor with a neutral floor cleaner following the product's directions. Burnish using the appropriate pads.

**RECOATING:** Dust mop & wash floor with a neutral floor cleaner following the product's directions. Apply 1-2 liberal coats of **GLAZE** using a mop.

## TECHNICAL DETAILS

SIZE	PACKAGING	LIQUID COLOR
1 GL	4/1 GL CASE	CLEAR
5 GL	PAIL	CLEAR

**Have a whole lot more to clean?**

Call us today to learn about our line of products!

**1-877-4-EMULSO**

2750 kenmore avenue, tonawanda, ny 14150 | [Emulso.com](http://Emulso.com)