

AR-92

Asphalt Release Agent

ALL SLICK, NO STICK.

AR-92 uses a high-performance formula to prevent asphalt from adhering to vehicles, machinery & equipment.

p/n	description	size
G5-05	Asphalt Release Agent	5 GL
G5-55	Asphalt Release Agent	55 GL
G5-275	Asphalt Release Agent	275 GL



FOR USE ON: TRUCK BEDS | SPREADER BARS | TOOLS | EQUIPMENT



FEATURES

- Foaming Solution Prevents Asphalt from Sticking to Surfaces
- Does Not Affect Asphalt Composition
- Highly-concentrated Formula
- Water-soluble



AR-92 is evaluated by the NTPEP
National Transportation Product Evaluation Program

DIRECTIONS

Dilute 1 part **AR-92** to 40 parts water. The surface to be treated must be clean of all residue and asphalt accumulation. Apply to truck bed, sidewalls, and spreader bar prior to loading with asphalt. **AR-92** should be dispensed through standard proportioning valves. *For best results, fill truck while the coating is still wet.*

TECHNICAL DETAILS

COLOR	ODOR	pH	FOAM	FLASH POINT	RINSABILITY	STABILITY/STORAGE	EMULSIFICATION	SOLUBILITY	PHOSPHATE CONTENT
Yellow	Mild	7 - 8	High	None	Complete	2 Years	Complete	100%	None

Have a whole lot more to clean?

Call us today to learn about our line of industrial cleaners & private label capabilities!

716.854.2889

2750 kenmore avenue, tonawanda, ny 14150 | Emulso.com