

AR-92

Asphalt Release Agent

ALL SLICK, NO STICK.

AR-92 uses a high-performance formula to prevent asphalt from adhering to vehicles, machinery & equipment.

- Foaming Solution Prevents Asphalt from Sticking to Surfaces
- Does Not Affect Asphalt Composition
- Highly-concentrated Formula
- Water-soluble
- Biodegradable



HIGH-PERFORMANCE FORMULA WILL NOT AFFECT ASPHALT COMPOSITION!



WHERE TO USE

- TRUCKS • SPREADER • BARS • TOOLS • EQUIPMENT

DIRECTIONS

READ ENTIRE PRODUCT LABEL PRIOR TO USE.

Dilute 1 part **AR-92** to 40 parts water. The surface to be treated must be clean of all residue and asphalt accumulation. Apply to truck bed, sidewalls, and spreader bar prior to loading with asphalt. **AR-92** should be dispensed through standard proportioning valves. *For best results, fill truck while the coating is still wet.*

TECHNICAL DETAILS

SIZE	PACKAGING	LIQUID COLOR
1 GL	4/1 GL CASE	YELLOW
5 GL	PAIL	YELLOW
55 GL	DRUM	YELLOW
275 GL	TOTE	YELLOW

Have a whole lot more to clean?

Call us today to learn about our line of products!

1-877-4-EMULSO

2750 kenmore avenue, tonawanda, ny 14150 | Emulso.com