

GLENZOIL 20 PLUS



CRACK SEALANT BARRIER MATERIAL

GLENZOIL 20 PLUS forms a protective barrier between freshly laid hot-melt crack sealants and tires, allowing traffic immediate access to roadways after repairs. Formulated for direct application to the surface of freshly applied hot-melt crack and joint sealants, GLENZOIL 20 PLUS uses a biodegradable liquid formula that will not affect the road surface or crack sealant composition or performance. **ALL SLICK, NO STICK.**

p/n	description	size
G7-5G	Glencoil 20 Plus	5 GL
G7-55	Glencoil 20 Plus	55 GL

FEATURES

- Prevents Sealant from Picking & Tracking
- Reduces Roadway Downtime
- Easy, One-person Application
- Ready-to-use

DIRECTIONS



Spray **GLENZOIL 20 PLUS** directly onto the surface of freshly applied hot-melt crack sealant using a handheld pump sprayer. There is no specific time interval required between the application of the sealant and the product. Rate of application varies depending on ambient & surface temperature, depth, width and frequency of cracks, traffic volume, and the distance of shadow vehicles.

TECHNICAL DETAILS

COLOR	ODOR	pH	FOAM	FLASH POINT	RINSABILITY	STABILITY/STORAGE	EMULSIFICATION	SOLUBILITY	PHOSPHATE CONTENT
Amber	Mild	N/D	None	None	Complete	2 Years	Complete	100%	None

Have a whole lot more to clean?

Call us today to learn about our line of industrial cleaners & private label capabilities!

716.854.2889

2750 kenmore avenue, tonawanda, ny 14150 | Emulso.com

