

RESILIENCE

Floor Finish

RESILIENCE uses a metal cross-linked acrylic-based formula to reduce finish dry time and maintenance intervals and leaves behind a high gloss shine. **RESILIENCE** is formulated to be buffed once a week or less.

- Seals Floors with a High Gloss Finish
- Fast Dry Time
- 22% Solids



EASY MAINTENANCE! BUFF ONCE WEEKLY AFTER APPLICATION



WHERE TO USE

- FLOORS

DIRECTIONS

READ ENTIRE PRODUCT LABEL PRIOR TO USE.

GENERAL APPLICATION: Apply **RESILIENCE** evenly on clean floor with a mop or applicator. Allow coat to dry at least 30 minutes before applying another coat.

FIRST-TIME USERS: Apply 2-3 layers of **RESILIENCE** to floors to establish a base coat.

MAINTENANCE: To maintain finish after initial application, use a quality floor cleaner and damp mop on a regular basis to maintain cleanliness and shine. Damaged floors and surfaces may require a pre-cleaning or finish stripping prior to **RESILIENCE** application.

TECHNICAL DETAILS

| SIZE | PACKAGING | LIQUID COLOR |
|-------|-------------|--------------|
| 1 GL | 4/1 GL CASE | WHITE |
| 5 GL | PAIL | WHITE |
| 55 GL | DRUM | WHITE |

Have a whole lot more to clean?

Call us today to learn about our line of products!

1-877-4-EMULSO

2750 kenmore avenue, tonawanda, ny 14150 | Emulso.com